MAX-LED KARTA PRODUKTOWA

Naświetlacze LED STAR PREMIUM 70W



www.max-led.pl

ZASTOSOWANIE

- Oświetlenie budynków
- Oświetlenie reklam
- Oświetlenie billboardów
- Oświetlenie parkingów

Dane techniczne podstawowe


Temperatura barwowa	EAN	Strumień świetlny
4500K biała neutralna	5901812469311	5740 lm *

Dane techniczne wspólne


Trzonek	-
Moc znamionowa	70 W
Moc odpowiednika	
Napięcie	220-240V
Kąt świecenia	120°
Klasa szczelności obudowy	IP65
Współczynnik oddawania barw	Ra ≥ 80
Współczynnik mocy	PF 0.9
Sposób montażu	outdoor
Możliwość ściemniania	NIE
Trwałość	50 000 h
Liczba cykli włączeniowych	20 000
Typ diod LED	SMD
Materiał	aluminium
Kolor obudowy	czarny
Czas rozruchu	<0,2s
Czas rozgrzewania do (60%), do (95%)	<2s

* Całkowity strumień świetlny źródła światła za kloszem przy temp. otoczenia 25°C. Tolerancja strumienia świetlnego +/- 10%.

Rysunek techniczny



Rysunek poglądowy sposób pakowania




Wymiary produktu

X - wymiar	277 [mm]
Y - wymiar	321 [mm]
Z - wymiar	40 [mm]

Opakowanie jednostkowe produktu

ox - wymiar	305 [mm]
oy - wymiar	360 [mm]
oz - wymiar	80 [mm]
Waga	2,15 [kg]

Diagram rozkładu natężenia światła



Opakowanie zbiorcze produktów

Typ pakowania (XYZ)	
Ilość sztuk	4
OX - wymiar	325 [mm]
OY - wymiar	295 [mm]
OZ - wymiar	360 [mm]
Waga	9,0 [kg]

WSZELKIE PRAWA ZASTRZEŻONE 2016 © GRUPA MAROX SP. Z O.O. SP. K.
GRUPA MAROX SPÓŁKA Z OGRANICZONĄ ODPOWIEDZIALNOŚCIĄ SPÓŁKA KOMANDYTOWA
POLAND, GOSPODARCZA 24, 32-600 OŚWIĘCIM

Zdjęcia produktów i niektóre parametry techniczne umieszczone w karcie produktu mogą nieznacznie odbiegać od produktów znajdujących się w sprzedaży. Zastrzegamy sobie prawo do błędów w druku.

MAX-LED PRODUCT CARD

LED FLOODLIGHT STAR PREMIUM 70W



MAXLED® lighting technologies

A+

www.max-led.pl

MAX-LED WARRANTY 3 years EXCLUSIVE

Star

APPLICATION

- buildings lighting
- advertising lighting
- bilboard lighting
- parking lighting

Basic technical data


Color temperature	EAN	Luminous flux
4500K neutral white	5901812469311	5740 lm *

Common technical data

Base	-
Wattage	70 W
Equivalent	
Voltage	220-240V
Beam angle	120°
IP protocol	IP65
Color Rendering Index	Ra ≥ 80
Power factor	PF 0.9
Mounting	outdoor
Dimming	No
Lifespan	50 000 h
Number of switching cycles	20 000
LED type	SMD
Material	aluminum
Housing color	black
Starting time	<0,2s
Warm-up time (60%), do (95%)	<2s

* The total luminous flux of the light source behind the shade at ambient temp. 25 ° C. Tolerance flux +/- 10%.


Technical drawing




Product dimensions

X - dimension	277 [mm]
Y - dimension	321 [mm]
Z - dimension	40 [mm]

Diagram of light intensity distribution



Illustrative method of packaging



The unit package of the product

ox - dimension	305 [mm]
oy - dimension	360 [mm]
oz - dimension	80 [mm]
Weight	2,15 [kg]

Packaged products

Packaging type (XYZ)	
Quantity	4
OX - dimension	325 [mm]
OY - dimension	295 [mm]
OZ - dimension	360 [mm]
Weight	9,0 [kg]

ALL RIGHTS RESERVED 2016 © GRUPA MAROX SP. Z O.O. SP. K.
GRUPA MAROX SPÓŁKA Z OGRANICZONĄ ODPOWIEDZIALNOŚCIĄ SPÓŁKA KOMANDYTOWA
POLAND, GOSPODARCZA 24, 32-600 OŚWIĘCIM

THE PICTURES OF PRODUCTS IN THE PRODUCT CARD MAY DIFFER FROM THE ACTUAL PRODUCTS. WE RESERVE THE RIGHT TO PRINTING MISTAKES AND ERRORS. THE SHAPE AND TECHNICAL DATE OF ALL PRODUCTS FROM THIS PRODUCT CARD ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.